


- ⊗ Wavelength: 750 ±5 nm
- ⊗ Output Power: Up to 2000mW free space, Up to 1600mW fiber coupled
- ⊗ High output power and dynamic range
- ⊗ High efficiency
- ⊗ Custom packaging available
- ⊗ Custom wavelengths and laser designs are available.



The LDX-3210-750 is a high power, infrared laser diode chip. The InAlGaAs laser design offers low divergence, high brightness, and proven reliability. Applications include solid-state laser pumping, materials processing, and medical applications.

These lasers are available in a variety of industry-standard packages, such as C-mount, B-mount, Q-mount, 9mm window package, and TO-3 window package. Also available in an HHL package incorporating an internal thermoelectric cooler, with optional fiber coupling. Custom package options are also available.

### Device Ratings

Parameter	Min.	Typ.	Max.	Units
Output Power		2000		mW
Operating Current			2200	mA
Operating Temperature		25		°C
Aperture Size		100		um
Polarization		TM		

### Device characteristics at 25°C and Rated Power:

Parameter	Min.	Typ.	Max.	Units
Forward Voltage		1.9		V
Wavelength		750 ±5 nm		nm
Spectral Width		1.1		nm
Divergance - Perpendicular		26		° (FWHM)
Divergance - Parrallel		6		° (FWHM)
Threshold Current		575		mA

All values are typical for a device packaged on C-mount  
 All device characteristics are subject to change