

Fiber-coupled diode laser stacks: cw, actively cooled with deionized water JOLD-140-CAXF-6A

Design 211615226

Features

- High optical output power of 140 W cw
- Wavelengths: 807, 915, 938 and 976 nm
- Fiber core diameter: 600 μm (NA 0.22)
- Integrated pilot laser and power monitor
- Lifetime > 10,000 h, high reliability

Applications

- Pumping of solid-state lasers and fiber lasers
- Material processing


Fiber-coupled diode laser stacks | cw, actively cooled with deionized water JOLD-140-CAXF-6A

Specifications (start of life)		F-6A Design 211615226			
Operation Mode	cw, power modulation only between threshold and maximum current				
Maximum Optical Output Power	140	140	140	140	W
Center Wavelength at 25 °C	807	915	938	976	nm
Center Wavelength Variation at 25 °C	3	5	5	3	nm
Typical Spectral Bandwidth (FWHM)	4	4	4	4	nm
Maximum Spectral Bandwidth (FWHM)	5	5	5	5	nm
Typical Operation Current	40	42	42	44	А
Maximum Operation Current	45	47	47	47	A
Typical Threshold Current	7	6	6	6	A
Maximum Threshold Current	10	7	9	9	A
Typical Slope	4.3	3.9	3.9	3.7	W/A
Minimum Slope	3.6	3.4	3.4	3.4	W/A
Maximum Operating Voltage	13	13	13	13	V
Fiber Core Diameter, Numerical Aperture	600 µm, NA 0.2	2			
Fiber Connection	High-power plug with 10 mm ferrule diameter				
Power Monitor	Infineon, SFH 229				
Pilot Laser	0.5 3 mW, 650 nm \pm 15 nm, 3 5 V, 40 \pm 15 mA, power not adjustable (only for teaching and targeting purposes before laser operation)				
Anode, Cathode Connectors	Plug KST6AR-N/10 (Part No.15.0001-22), Socket KBT6AR-N/10-S (Part No. 15.0017-21); Ref.: www.multi-contact-usa.com				
Humidity Reduction	Purge gas, water vapor outlet closed with membrane				
Purge Gas	Synthetic air, purity > 99.9997 %, flow rate 0.1 0.5 l/h (10 20 mbar pressure), Ref.: www.airliquide.com				
Purge Gas Connector	Ø 4 mm push-in fitting				
Expected Lifetime	> 10,000 h (constant current)				
Cooling					
Flow Rate	2.3 l/min ± 0.2 l/min				
Water Temperature	15 35 ℃				
Water Pressure	400 kPa maximum inlet and outlet pressure, 150 250 kPa pressure drop				
Water Connectors	Ø 8 mm push-in fittings				
Water Quality	Deionized 2 6 μ S/cm, mixed bed ion exchanger, particle filter < 25 μ m (not included)				


JENOPTIK

See general user information!

Options on request: Including dry cartridge instead of water vapour outlet







 **) required connector: KBT6AR-N/ 10-S; Order No. 15.0017-(Fa: MULTI-CONTACT)
***) external diameter of waterhose must be calibrated with a size of 8 mm

calibrated with a size of 8 mi ambient temperature < 40 °C 11/2017 | Specifications may change in compliance with our quality management system.