

# Quantas

## Q2-1053

## HIGH ENERGY AIR-COOLED Q-SWITCHED LASER

### FEATURES

---

Up to **100 mJ** pulse energy

---

**Air cooled** (no water)

---

**20 Hz** repetition rate

---

Built-in sync pulse generator for triggering of user equipment

---

Remote monitoring and control via built-in **Ethernet / WiFi** interface

---

Optional 2<sup>nd</sup>, 3<sup>rd</sup>, 4<sup>th</sup> or 5<sup>th</sup> smart harmonic generators

---

Optional attenuator for fundamental wavelength

---

Guaranteed **> 1 Gshot** lifetime

### APPLICATIONS

---

Light Induced Breakdown Spectroscopy (LIBS)

---

OPO, dye laser, Ti:sapphire pumping

---

Remote sensing

---

Laser ablation

---

Time-of-Flight Spectroscopy (TOFS)

---

Light Induced Fluorescence (LIF) Spectroscopy

---

Flash photolysis

---

Matrix Assisted Laser Desorption / Ionization (MALDI)

---

Pulsed light deposition (PLD)



Quantas Q2 models set new standard in Q-switched laser market. Q2 series diode pumped, fully air-cooled, Q-switched lasers are designed for wide range of applications that require high peak power pulses. Robust, reliable design is what makes this series ideal tool for applications like Light Induced Breakdown Spectroscopy (LIBS), LCD repair, laser ablation, remote sensing and many others. Two models are available offering 70 mJ @ 10 Hz or 100 mJ @ 20 Hz pulse energies.

Less than 10 ns pulse duration allows efficient fundamental wavelength conversion to higher harmonics with shortest wavelength available of 211 nm. Wavelength extensions into infrared range by use of OPO are available by request.

TEC based cooling eliminate risks associated with water cooling (like leaks, circuit shortening etc.) as well as reduce running cost due to no maintenance required.

Low jitter triggering pulses for user equipment are available with up to 450  $\mu$ s lead in internal triggering mode. If required, laser pulsing can be externally triggered from delay generator.

Laser controlled via built-in Ethernet port through web-server with option to add Wi-Fi adapter. It allows users to monitor and control laser remotely.



Quantum  
Light  
Instruments

---

[WWW.QLINSTRUMENTS.COM](http://WWW.QLINSTRUMENTS.COM)

## SPECIFICATIONS <sup>1)</sup>

MODEL	Quantas Q2-1053	
	Q2-10	Q2-20HE
Wavelength	1053 nm	
Pulse energy	70 mJ	100 mJ
Typical pulse duration	<10 ns <sup>2)</sup>	
Pulse to pulse energy stability	<0.5 % RMS <sup>3)</sup>	
Power drift	± 3.0 % <sup>4)</sup>	
Maximum pulse repetition rate <sup>5)</sup>	10 Hz	20 Hz
Beam profile	bell-shaped, >75 % fit to Gaussian	
Beam divergence <sup>6)</sup>	< 4 mrad	
Polarization	linear, horizontal	
Typical beam diameter <sup>7)</sup>	3.5 mm	
Jitter	< 1 ns RMS <sup>8)</sup>	

### OPTIONAL HARMONICS GENERATOR MODULE <sup>9)</sup>

Pulse energy, mJ	Q2-10	Q2-20HE
526 nm	35 mJ	50 mJ
351 nm	20 mJ	30 mJ
263 nm	11 mJ	15 mJ
211 nm	3.5 mJ	6 mJ

### OPTIONAL ATTENUATOR <sup>10)</sup>

Wavelength, nm	1053 nm, 526 nm, 351 nm
Attenuation range	5 – 95 %

### DIMENSIONS

Laser head (W×L×H)	190 × 408 × 120 mm <sup>3</sup>
Harmonics generator module (W×L×H)	113 × 242 × 112 mm <sup>3</sup>
Controller unit (W×L×H)	160 × 104 × 55 mm <sup>3</sup>
Power adapter, typical (W×L×H)	100 × 200 × 50 mm <sup>3</sup>

### OPERATING REQUIREMENTS

Cooling requirements	air cooled
Ambient temperature	15 – 30 °C
Relative humidity	10 – 80 % (non-condensing)
Mains voltage	90 – 230 V AC, single phase, 47 – 63 Hz <sup>11)</sup>
Power consumption	100 W

<sup>1)</sup> Due to continuous improvements all specifications are subject to change. Unless stated otherwise all specifications are measured at 1053 nm and maximum pulse repetition rate.

<sup>2)</sup> FWHM level at 1053 nm. Shorter pulse duration is available by request. Inquire for detailed specifications.

<sup>3)</sup> Averaged from 30 second time interval.

<sup>4)</sup> Over 8 hour period after 20 minutes of warm-up when ambient temperature variation is less than ±2 °C.

<sup>5)</sup> Factory-set pulse repetition rate is fixed at 10 Hz or 20 Hz, depending on model. Variable pulse repetition rate is possible when laser is externally triggered.

<sup>6)</sup> Full angle measured at the 1/e<sup>2</sup> level.

<sup>7)</sup> Beam diameter is measured 20 cm from laser output at the 1/e<sup>2</sup> level.

<sup>8)</sup> In respect to Q-switch triggering edge of pulse.

<sup>9)</sup> Harmonics generator module is stand-alone unit optimized for specified output wavelength. Inquire for details if you need multiple wavelength output.

<sup>10)</sup> Attenuator is build-in into harmonics generator module.

<sup>11)</sup> Laser can be powered from appropriate 28 V DC power source. Inquire for details.



## DRAWINGS

